

Product Release

LWW-90R75W-GA (GREEN & AMBER)

LED Dual Color Beacon (All images are illustration only)
Barcode: 9342828166263



WELDEX
CORPORATION



[Green LED On]



[Amber LED On]

Features

- Default pattern is Rotary (4 different flashing patterns are optional)
- Circular LED discs for intense, 360° visible light output
- Impact-resistant PC lens system
- Heavy-duty cast alloy base & cap
- Multi-stage paint coating for UV & corrosion protection
- Fully sealed & pre-wired to prevent dirt & moisture
- Low EMC signature (CISPR class 3)
- Surface mounting type
- Lead wire type

Dual Color Function



[Green & Amber]

Specification

Wattage		Input voltage	IP rating
84 W(flash each Green & amber 42W), 32 W(rotary each Green & amber 16W)		DC 10~36 V	IP69K
Operating temperature	Vibration rating	Housing color	
-40°C ~ +80°C	60 G	Amber	
LED color	Lifespan	Frequency rotating	Weight
Green & Amber	50,000hrs	134 cycles/min.	1.3 kg

Wiring Option

- Amber single function
- Green single function
- Dual green-amber simultaneously (180 degree apart) Function
- NOTE : Installation of change over relay is required to enable the beacon to offer both colours independently on vehicle

Dimensions

[Unit: mm]

