

CONTINUOUS DUTY SOLENOIDS

SINGLE PACK



24059BX

12V 85A CONTINUOUS DUTY SOLENOID
N/O CONTACTS



- Continuous Rating: 85A, SPST
- Material: Plated steel case
- Contacts: Copper
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 84mm



24213BX

12V 200A CONTINUOUS DUTY SOLENOID
N/O CONTACTS



- Continuous Rating: 200A, SPST
- Material: Plated steel case
- Contacts: Silver
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 84mm



24063BX

24V 85A CONTINUOUS DUTY SOLENOID
N/O CONTACTS



- Continuous Rating: 85A, SPST
- Material: Plated steel case
- Contacts: Copper
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 84mm



24214BX

24V 200A CONTINUOUS DUTY SOLENOID
N/O CONTACTS



- Continuous Rating: 200A, SPST
- Material: Plated steel case
- Contacts: Silver
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 84mm



M24117BX

12V 85A CONTINUOUS DUTY
SOLENOID N/O CONTACTS



- Continuous Rating: 85A, SPST
- Material: Plated steel case, PVC sealed
- Contacts: Silver
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- UL Listed
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 84mm



24063-08BX

24V 85A CONTINUOUS DUTY
SOLENOID N/O CONTACTS



- Continuous Rating: 85A, SPST
- Material: Plated steel case, PVC sealed
- Contacts: Silver
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- UL Listed
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 84mm

