

ROCKER SWITCHES

SINGLE PACK



58328-62BX

24V ROCKER SWITCH ON/OFF
ILLUMINATES AMBER WITH LOAD



- 24V
- Material: Plastic, silver contacts
- Position: On/Off, SPST
- 3 x Blade terminal
- Rating: 12A @ 24Vdc
- Mounting hole: 36.8 x 21.1mm
- Panel thickness: 2.4 - 4.7mm
- Illumination: Amber



58328-58BX

24V ROCKER SWITCH ON/OFF
ILLUMINATES RED WITH LOAD



- 24V
- Material: Plastic, silver contacts
- Position: On/Off, SPST
- 3 x Blade terminal
- Rating: 12A @ 24Vdc
- Mounting hole: 36.8 x 21.1mm
- Panel thickness: 2.4 - 4.7mm
- Illumination: Red
- Independent illumination



58312-A4BX

ROCKER SWITCH OFF/ON
ILLUMINATES AMBER WITH LOAD



- Rating: 12/24V (24V requires reducer resistor)
- Material: Plastic, silver contacts
- Position: Off/On, SPST
- 3 x Blade terminal
- Rating: 25A @ 12Vdc
- Mounting hole: 36.8 x 21.1mm
- Panel thickness: 2.4 - 4.7mm
- Illumination: Amber



58312-G4BX

ROCKER SWITCH OFF/ON
ILLUMINATES GREEN WITH LOAD



- Rating: 12/24V (24V requires reducer resistor)
- Material: Plastic, silver contacts
- Position: Off/On, SPST
- 3 x Blade terminal
- Rating: 25A @ 12Vdc
- Mounting hole: 36.8 x 21.1mm
- Panel thickness: 2.4 - 4.7mm
- Illumination: Green



58312-R4BX

ROCKER SWITCH OFF/ON
ILLUMINATES RED WITH LOAD



- Rating: 12/24V (24V requires reducer resistor)
- Material: Plastic, silver contacts
- Position: Off/On, SPST
- 3 x Blade terminal
- Rating: 25A @ 12Vdc
- Mounting hole: 36.8 x 21.1mm
- Panel thickness: 2.4 - 4.7mm
- Illumination: Red



58326-18BX

ROCKER SWITCH OFF/ON,
DUAL ILLUMINATION
WITH STROBE SYMBOL



- Rating: 12/24V
- Material: Plastic, silver contacts
- Position: Off/On, SPST
- 5 x Blade terminal
- Rating: 20A @ 12Vdc
- Mounting hole: 36.8 x 21.1mm
- Panel thickness: 2.4 - 4.7mm

