


KL600 SERIES



1708	■ Blue - Pipe Mount, 12V DC
1709	■ Red - Pipe Mount, 12V DC (Optic Lens)
1710	■ Amber - Pipe Mount, 12V DC
1711	■ Blue - Pipe Mount, 24V DC
1712	■ Red - Pipe Mount (Optic Lens), 24V DC
1713	■ Amber - Pipe Mount (Optic Lens), 24V DC Amber Base

Voltage	12V DC (globe included) 24V DC (globe included)	
Current Draw	12V DC - 5A 24V DC - 3.5A	
Wattage	12V DC - 55W 24V DC - 70W	
Rotation	160 +/- 30 rpm.	
Mounting	Pipe Mounting. Tubular base incorporates connection plug. Must be used in conjunction with connecting piece Part No. 8007, or other HELLA 2-pole beacon mounts. (see page 177) ①	
Globe to suit	12V H1 (C1255) 24V H1 (C2470)	
Note	1710 version shown	
Accessories	8007 8007FM 8007RA 8007SCR	2-Pole Beacon Mount 2-Pole Beacon Mount – Flat 2-Pole Beacon Mount – 90° 2-Pole Beacon Mount – Screw
Spare Parts	9.1708.01 9.1701.01 9.1709.01 9.1710.01 9.1713.01 9.1717.52 9.1720.52 9.1717.23 9.1717.54 9.1720.54 9.1737.91	■ Blue Lens ■ Red Lens ■ Red Lens (optic) ■ Amber Lens ■ Amber Lens (optic) 12V Motor with reflector (clip mount) ② 24V Motor with reflector (clip mount) ② Reflector Base Assembly (screw mount) ③ 12V Motor (plastic type) ④ 24V Motor (plastic type) ④ Drive Belts (set of 2) ⑤