

BATTERY MASTER SWITCH

SINGLE PACK/KIT

Baxters
THE DRIVING FORCE IN AUTOMOTIVE SOLUTIONS

TSW24VI

24V BATTERY MASTER SWITCH
T HANDLE ON/OFF POSITIVE
FAIL SAFE



- Fail safe trip. can be tripped with loss of V & signal @ Pin 1 of Green Connector
- Type: DPST N/O
- IP rating: IP67
- Cont. current: 500A
- Max. current 5 sec.: 3000A
- Max. current 30 sec.: 2250A
- External trigger: 10A
- Ex rating: EX & CE Certified
- Aux. contacts: 2 x N/O
- Operating voltage: 18 - 30VDC
- Auxiliary 1 circuit: 10A
- Auxiliary 2 circuit: 10A



TSW12K

12V BATTERY MASTER SWITCH
T HANDLE ON/OFF



- Type: DPST N/O
- IP rating: IP67
- Cont. current: 500A
- Max. current 5 sec.: 3000A
- Max. current 30 sec.: 2250A
- External trigger: 10A
- Ex rating: EX & CE Certified
- Aux. contacts: 2 x N/O
- Operating voltage: 9 - 15VDC
- Auxiliary 1 circuit: 10A
- Auxiliary 2 circuit: 10A



TSW12PK

12V BATTERY MASTER SWITCH
POSITIVE/POSITIVE T HANDLE
ON/OFF



- Type: DPST N/O
- IP rating: IP67
- Cont. current: 500A
- Max. current 5 sec.: 3000A
- Max. current 30 sec.: 2250A
- External trigger: 10A
- Ex rating: EX & CE Certified
- Aux. contacts: 2 x N/O
- Operating voltage: 9 - 15VDC
- Auxiliary 1 circuit: 10A
- Auxiliary 2 circuit: 10A



TSW24VEC

24V BATTERY MASTER SWITCH
ON/OFF



- Type: DPST N/O
- IP rating: IP67
- Cont. current: 500A
- Max. current 5 sec.: 3000A
- Max. current 30 sec.: 2250A
- External trigger: 100A
- Ex rating: EX & CE Certified
- Aux. contacts: 1 x N/C; 1 x N/O
- Operating voltage: 18 - 30VDC
- Auxiliary 1 circuit: 10A
- Auxiliary 2 circuit: 10A



TSW24VCO

24V BATTERY MASTER SWITCH
T HANDLE ON/OFF



- Type: DPST N/O
- IP rating: IP67
- Cont. current: 500A
- Max. current 5 sec.: 3000A
- Max. current 30 sec.: 2250A
- External trigger: 10A
- Ex rating: EX & CE Certified
- Aux. contacts: 1 x N/O; 1 x N/C
- Operating voltage: 18 - 30VDC
- Auxiliary 1 circuit: 10A
- Auxiliary 2 circuit: 10A



BMS-PKIT

CONNECTOR KIT TO SUIT DPS & TSW SWITCHES

- Connector Kit to Suit DPS & TSW Switches

