RSM5454 SERIES

ROADVISION



- Multi-volt 10-30V input & low current draw
- · Built-in 10 selectable flash patterns
- · Last pattern memory recall
- 100,000 hour LED life span with solid state technology
- Maintenance free
- · Multi-unit synchronisation
- Simultaneous or alternating flashing
- · Weatherproof & vibration resistant
- · Super low-profile for discrete applications















ROADVISION'S RSM5454 Series super low-profile LED strobe modules are simply perfect for discrete applications! Roadvision's super bright LED strobe modules deliver the durability of maintenance free LED technology and greater visibility. Featuring 10 selectable flash patterns, multi-unit synchronisation (simultaneous or alternating flash), aluminium housing and virtually unbreakable polycarbonate lens. Roadvision's RSM5454 Series modules simply take safety lighting to another level, ideal for all your automotive, industrial and agricultural requirements.

PART NUMBERS




RSM5454W LED Strobe Module 10-30V Square Surface Mount 12W White



RSM5454A LED Strobe Module 10-30V Square Surface Mount 12W Amber

SPECIFICATIONS	RSM5454W	RSM5454A
SYNCHRONISATION	Simultaneous & Alternate	Simultaneous & Alternate
FLASH PATTERNS	10	10
INPUT VOLTAGE	10-30 VDC	10-30 VDC
WATTS	12W	12W
NUMBER OF LEDS	4x 3W	4 x 3W
CURRENT DRAW @ 13.8V	1 Amp	1 Amp
LENS CONSTRUCTION	Polycarbonate	Polycarbonate
HOUSING CONSTRUCTION	Aluminium	Aluminium
MOUNTING CENTRES	64mm	64mm
DIMENSIONS AXBXC	75 x 55 x 14mm	75 x 55 x 14mm
WIRING	Red - Positive	Red - Positive
	Black - Negative	Black - Negative
	Green - Flash Select & Sync	Green - Flash Select & Sync
	White - Alternate Flash	White - Alternate Flash

LINE DIAGRAM



FLASH PATTERNS

LUSU LAITEKNS		
1	Single	
2	Single, California Title 13	
3	Double	
4	Triple	
5	Quadruple	
6	Quintuple	
7	Combination Single/Double	
8	Combination Single/Triple	
9	Combination Single/Quintuple	
10	Strobe	
11	Cruise (30% Brightness)	