

SURFACE MOUNT SOCKETS

SINGLE PACK

LV1734

SURFACE MOUNT ACCESSORY SOCKET NO LED BACKLIGHT

- Voltage: 12/24V
- Current rating: 20A@12V
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 55(W) x 50(H) x 80(D)mm
- Cnt to cnt: 40.8mm



LV1775

SURFACE MOUNT ACCESSORY SOCKET BLUE LED BACKLIGHT

- Voltage: 12/24V
- Current rating: 20A@12V
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 55(W) x 50(H) x 80(D)mm
- Cnt to cnt: 40.8mm



LV1775W

WHITE SURFACE MOUNT ACCESSORY SOCKET BLUE LED BACKLIGHT

- Voltage: 12/24V
- Current rating: 20A@12V
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 55(W) x 50(H) x 80(D)mm
- Cnt to cnt: 40.8mm
- Marine applications



LV1721

SURFACE MOUNT ACCESSORY SOCKET, NO LED BACKLIGHT

- Voltage: 12V
- Current rating: 20A@12V
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 55(W) x 40(H) x 73(D)mm
- Cnt to cnt: 40.8mm



SUTARS
- Since 1980 -



LV1778

SURFACE MOUNT ENGEL SOCKET BLUE LED BACKLIGHT

- Voltage: 12/24V
- Current rating: 20A@12V
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 55(W) x 50(H) x 80(D)mm
- Cnt to cnt: 40.8mm



LV1724

SURFACE MOUNT ENGEL SOCKET

- Voltage: 12/24V
- Current rating: 16A@12V
- Material: aluminium
- Terminals: 2 x Screw-on
- Dimensions: 57(W) x 26(H) x 41(D)mm
- Heavy duty applications

