

SINGLE PACK

## LV1890

### 10A 12/24VDC AUTO PWM SOLAR CHARGE CONTROLLER



- Latest intelligent microprocessor technology
- Automatic voltage detection
- USB output port 5V/1.2A
- LED indicators
- 3 stage intelligent charging: bulk, boost/equalise, float
- PWM charging circuit for higher efficiency
- Protected from overcharging, over-discharging & overloading
- Operating temperature: -35°C to +50°C
- Dimensions: 120 x 67 x 22mm




## LV1891

### 20A 12/24VDC AUTO PWM SOLAR CHARGE CONTROLLER



- Latest intelligent microprocessor technology
- Automatic voltage detection
- USB output port 5V/1.2A
- LED indicators
- 3 stage intelligent charging: bulk, boost/equalise, float
- PWM charging circuit for higher efficiency
- Protected from overcharging, over-discharging & overloading
- Operating temperature: -35°C to +55°C
- Dimensions: 148 x 86 x 35mm



## LV1892

### 30A 12VDC AUTO PWM SOLAR CHARGE CONTROLLER



- Latest intelligent microprocessor technology
- 3 stage intelligent charging: bulk, boost/equalise, float
- PWM charging circuit for higher efficiency
- Large LCD display for easy monitoring
- Protected from overcharging, over-discharging & overloading
- Operating temperature: -25°C to +40°C
- Dimensions: 165.5 x 96 x 41.4mm



## SCC075015060R

### 15A 12/24VDC MPPT 75/15 SMARTSOLAR CHARGE CONTROLLER



- Battery voltage: 12/24V
- Max. PV open circuit voltage: 75V
- Rated charge current: 15A
- Operating temperature: -30 to +60 °C
- Dimensions: 100 x 113 x 40mm



## SCC110030210

### 30A 12/24VDC MPPT 100/30 SMARTSOLAR CHARGE CONTROLLER



- Battery voltage: 12/24V
- Max. PV open circuit voltage: 100V
- Rated charge current: 30A
- Operating temperature: -30 to +60 °C
- Dimensions: 130 x 186 x 70mm



## SCC110050210

### 50A 12/24VDC MPPT 100/50 SMARTSOLAR CHARGE CONTROLLER



- Battery voltage: 12/24V
- Max. PV open circuit voltage: 100V
- Rated charge current: 50A
- Operating temperature: -30 to +60 °C
- Dimensions: 130 x 186 x 70mm

