


HEATSHRINK REFILLS

- Material: Polyolefin
- Ratio: 2:1
- Max. rating: 300V
- Operating temperature: -55°C to +125°C
- UL VW-1 & CSA: flame retardant, self extinguishing
- Blister pack of 10



PACK OF 10



PRODUCT INFORMATION


Part No.	Inside Dia.	Colour	Length	Qty	Part No.	Inside Dia.	Colour	Length	Qty
LV3361	2mm	Black	50mm	10	LV3365R	10mm	Red	50mm	10
LV3361R	2mm	Red	50mm	10	LV3366	13mm	Black	50mm	10
LV3362	3mm	Black	50mm	10	LV3366R	13mm	Red	50mm	10
LV3362R	3mm	Red	50mm	10	LV3367	16mm	Black	50mm	10
LV3363	5mm	Black	50mm	10	LV3367R	16mm	Red	50mm	10
LV3363R	5mm	Red	50mm	10	LV3368	19mm	Black	50mm	10
LV3364	7mm	Black	50mm	10	LV3368R	19mm	Red	50mm	10
LV3364R	7mm	Red	50mm	10	LV3369	25mm	Black	50mm	10
LV3365	10mm	Black	50mm	10	LV3369R	25mm	Red	50mm	10

HEATSHRINK IN 1.2M LENGTH

- Material: Polyolefin
- Ratio: 2:1
- Max. rating: 300V
- Operating temperature: -55°C to +125°C
- UL VW-1 & CSA: flame retardant, self extinguishing
- Pack in cut length



CUT LENGTH



PRODUCT INFORMATION

Part No.	Inside Dia.	Colour	Length	Part No.	Inside Dia.	Colour	Length
LV3300	3mm	Black	1.2m	LV3316	13mm	Black	1.2m
LV3302	3mm	Red	1.2m	LV3318	13mm	Red	1.2m
LV3304	5mm	Black	1.2m	LV3320	19mm	Black	1.2m
LV3306	5mm	Red	1.2m	LV3322	19mm	Red	1.2m
LV3308	7mm	Black	1.2m	LV3324	25mm	Black	1.2m
LV3310	7mm	Red	1.2m	LV3326	25mm	Red	1.2m
LV3312	10mm	Black	1.2m	LV3328	40mm	Black	1.2m
LV3314	10mm	Red	1.2m				