

SINGLE PACK

interVOLT

## VOLTAGE STABILISERS 12-12VDC

- High visibility LED status display & diagnostic indicators
- Excellent line & load regulation output characteristics
- Highly stable under a range of adverse input voltage conditions
- Suitable for high temperature environments
- Made from corrosion resistant materials
- Compact in size with a unique mounting plate to reduce footprint
- C-Tick approved



### PRODUCT INFORMATION

Part No.	Input Voltage	Output Voltage	Continuous Rating	Dimensions	Weight
SVS1212050	11-17Vdc	12.5Vdc + 1%	5A	101 x 62 x 34mm	160g
SVS2424025	22-33Vdc	25.0Vdc + 1%	2.5A	101 x 62 x 34mm	160g

## MINI ISOLATED SWITCH MODE POWER CONDITIONERS

- Unique LED diagnostic indicator to assist with troubleshooting
- User selectable high or low voltage output (slide switch)
- Can be used as a float charger for standard lead acid batteries
- Galvanically isolated input to output - no common connectivity
- Precise voltage regulation & superior noise filtering circuitry
- Full electronic protection to ensure both longevity & safety
- C-Tick approved



### PRODUCT INFORMATION

Part No.	Input Voltage	Output Voltage	Continuous Rating	Dimensions	Weight
SPCI121207	10-16Vdc	12.5/13.6Vdc	7A	170 x 80 x 40mm	418g
SPCI242405	17-33Vdc	15.0/27.2Vdc	5A	170 x 80 x 40mm	418g

## GEN II MAXI ISOLATED SWITCH MODE POWER CONDITIONERS

- Unique LED indicators to assist with troubleshooting
- Special mode setting for charging an auxiliary battery (2 Stage)
- Remote control to turn unit on/off with signal current only
- Multifunction alarm output for fault & pre-emptive warnings
- Integrated speed & temperature controlled cooling fan
- Galvanically isolated input to output - no common connectivity
- Heavy duty termination with separate, removable terminal cover
- Compact design which can be mounted vertically or horizontally
- C-Tick approved



### PRODUCT INFORMATION

Part No.	Input Voltage	Output Voltage	Continuous Rating	Dimensions	Weight
SPCI121210G2	10.5-16Vdc	12-14Vdc	10A @ 40°C	170 x 110 x 55mm	830g
SPCI121220G2	10.5-16Vdc	12-14Vdc	20A @ 40°C	230 x 110 x 55mm	1.15kg
SPCI242410G2	20-33Vdc	24-28Vdc	10A @ 40°C	170 x 110 x 55mm	830g
SPCI242420G2	20-33Vdc	24-28Vdc	20A @ 40°C	230 x 110 x 55mm	1.15kg