

SURFACE MOUNT SOCKETS & GAUGES

SINGLE PACK



LV1795

TRIPLE SURFACE MOUNT ACCESSORY SOCKETS



- Accessory sockets x 3
- Voltage: 12/24V
- Current rating: 20A@12V
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 150(W) x 50(H) x 80(D)mm
- Cnt to cnt: 128.5mm



LV1748

TRIPLE SURFACE MOUNT ACCESSORY/ MERIT SOCKETS



- Accessory x 2 & merit x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 150(W) x 50(H) x 80(D)mm
- Cnt to cnt: 128.5mm



LV1798

TRIPLE SURFACE MOUNT ACCESSORY SOCKETS/VOLTMETER



- Accessory x 2 & voltmeter x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- Voltmeter reading: 5-30V
- Voltmeter: Red LED display
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 150(W) x 50(H) x 80(D)mm
- Cnt to cnt: 128.5mm



LV1797

TRIPLE SURFACE MOUNT ACCESSORY SOCKETS/TWIN OUTPUT USB PORT



- Accessory x 2 & twin USB port x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- USB current output: 5V/2.1A x 2
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 150(W) x 50(H) x 80(D)mm
- Cnt to cnt: 128.5mm



LV1749

TRIPLE SURFACE MOUNT ACCESSORY/ MERIT/VOLTMETER



- Accessory x 1, merit x 1 & voltmeter x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- Voltmeter reading: 5-30V
- Voltmeter: Red LED display
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 150(W) x 50(H) x 80(D)mm
- Cnt to cnt: 128.5mm



LV1796

TRIPLE SURFACE MOUNT ACCESSORY/ DIGITAL VOLTMETER/ TWIN OUTPUT USB PORT



- Accessory x 1, voltmeter x 1 & twin USB port x 1
- Voltage: 12/24V
- Voltmeter reading: 5-30V
- Material: Thermoplastic Nylon 66
- Red LED display
- USB current output: 5V/2.1A x 2
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 150(W) x 50(H) x 80(D)mm
- Cnt to cnt: 128.5mm

