





SINGLE CORE BATTERY CABLE

- Conductor: Oxygen free plain copper wire to AS/NZS 1125
- Insulation: V90 PVC to AS/NZS3808
- Voltage: 50Vac or 120Vdc
- Applications: Battery feeds, general purpose automotive wiring
- Insulation thickness: 0.6mm



ROLL

PRODUCT INFORMATION

Part No.	Size (B&S)	Area (mm ²)	Amp@30°C	Colour	Length (m)	Strands/Dia.	Resistance (Ohm/km)	O.D.(mm)	Mass (kg/100m)
CB108A1-030BK	8	7.71	74	Black	30	96/0.32	2.4	5.5	9.3
CB108A1-100BK	8	7.71	74	Black	100	96/0.32	2.4	5.5	9.3
CB108A1-500BK	8	7.71	74	Black	500	96/0.32	2.4	5.5	9.3
CB108A1-030RD	8	7.71	74	Red	30	96/0.32	2.4	5.5	9.3
CB108A1-100RD	8	7.71	74	Red	100	96/0.32	2.4	5.5	9.3
CB108A1-500RD	8	7.71	74	Red	500	96/0.32	2.4	5.5	9.3
CB106A1-030BK	6	13.5	103	Black	30	168/0.32	1.4	7.2	15.6
CB106A1-100BK	6	13.5	103	Black	100	168/0.32	1.4	7.2	15.6
CB106A1-030RD	6	13.5	103	Red	30	168/0.32	1.4	7.2	15.6
CB106A1-100RD	6	13.5	103	Red	100	168/0.32	1.4	7.2	15.6
CB104A1-030BK	4	20.26	135	Black	30	252/0.32	0.9	8.3	22.4
CB104A1-100BK	4	20.26	135	Black	100	252/0.32	0.9	8.3	22.4
CB104A1-030RD	4	20.26	135	Red	30	252/0.32	0.9	8.3	22.4
CB104A1-100RD	4	20.26	135	Red	100	252/0.32	0.9	8.3	22.4
CB103A1-030BK	3	26.45	168	Black	30	329/0.32	0.7	10.2	29.9
CB103A1-100BK	3	26.45	168	Black	100	329/0.32	0.7	10.2	29.9
CB103A1-030RD	3	26.45	168	Red	30	329/0.32	0.7	10.2	29.9
CB103A1-100RD	3	26.45	168	Red	100	329/0.32	0.7	10.2	29.9
CB102A1-030BK	2	32.07	188	Black	30	399/0.32	0.6	11.3	37.1
CB102A1-100BK	2	32.07	188	Black	100	399/0.32	0.6	11.3	37.1
CB102A1-030RD	2	32.07	188	Red	30	399/0.32	0.6	11.3	37.1
CB102A1-100RD	2	32.07	188	Red	100	399/0.32	0.6	11.3	37.1
CB101A1-030BK	1	39.55	210	Black	30	492/0.32	0.5	12.1	44.4
CB101A1-030RD	1	39.55	210	Red	30	492/0.32	0.5	12.1	44.4
CB110A1-010BK	0	49	246	Black	10	608/0.32	0.4	12.7	54.3
CB110A1-030BK	0	49	246	Black	30	608/0.32	0.4	12.7	54.3
CB110A1-010RD	0	49	246	Red	10	608/0.32	0.4	12.7	54.3
CB110A1-030RD	0	49	246	Red	30	608/0.32	0.4	12.7	54.3
CB100A1-010BK	2/0	64.15	292	Black	10	798/0.32	0.3	14.5	70.1
CB100A1-030BK	2/0	64.15	292	Black	30	798/0.32	0.3	14.5	70.1
CB100A1-100BK	2/0	64.15	292	Black	100	798/0.32	0.3	14.5	70.1
CB100A1-030RD	2/0	64.15	292	Red	30	798/0.32	0.3	14.5	70.1
CB000A1-010BK	3/0	83.19	335	Black	10	1035/0.32	0.23	16.4	94
CB000A1-030BK	3/0	83.19	335	Black	30	1035/0.32	0.23	16.4	94
CB000A1-030RD	3/0	83.19	335	Red	30	1035/0.32	0.23	16.4	94