

# PRODUCT RELEASE

## E65-1014 Digital Wireless Reverse Camera Kit

9" Quad Monitor 12/24V  
c/w One Camera

Barcode: 9342828153324

### Main Features

- The 4TX to 1RX waterproof digital wireless system is specially designed for commercial vehicle such as truck, trailer and farm cultivator.
- With significant long-distance and stable transmission capacity, the transmission range can be as far as 120M.
- Waterproof & Dust Resistance Grade: IP65
- Applicable for DC 12V/24V vehicle
- With re-pairing function
- With record function
- Day/ night sensor for automatic adjustment
- Build-in speaker

\* **Additional camera sold separately**



E65-1009

### Technical Data For Wireless Monitor:

- 9 inch Digital TFT LCD monitor, 16:9
- Video input & video output: 4CH
- Wide view angle (CR>10): (up/ down): 50/70, (left/right): 70/70
- High brightness (cd/m2): 400
- Contrast ratio: 500
- Resolution: 800 x 3 (RGB) x 480
- Frequency range: 2406 - 2476 MHz
- Barrier-free transmission distance: ≤120M (free sight)
- Memory mode: high speed SD card Max. 128GB
- Start up time: 1S Max
- Latency: < 120 ms
- Video code: MPEG4
- Audio code: WAV, 1 channel
- Frame rate: NTSC: 30f/s PAL: 25f/s
- Color system: PAL/NTSC
- Waterproof & dust resistance grade: IP65
- Power requirement: 12V/24V DC
- Power consumption: ≤8W
- Operating temperature: -20°C to +70°C
- Storage temperature: -30°C to +80°C
- Dimension: 226(L) x 156(W) x 31(D) mm
- Weight: 1050± 50g

### Technical Data For Wireless Camera:

- Image type: 1/3 Inch CMOS
  - Resolution (pixels): 750 x 500
  - Lens angle: 85°(D) or 126°(D)
  - Minimal illumination: 0Lux/F2.6 (Automatic IR LED)
  - 20 x LED, for night vision > 8m
  - Modulation: 2.4G FHSS
  - Launching power: 10Mw/CE/2Mw/FCC
  - Transmission distance: 120m
  - Channel frequency: 20 Channel A/V auto switch
  - Operating frequency: 2406 - 2476 MHz
  - Waterproof and dust resistance grade: IP68
  - Horizontal resolution: 500 TV Lines
  - Power supply: 9V-30V DC
  - Power consumption: ≤2.5W
  - Signal to noise ratio: > 48dB
  - Operating temperature range: -10°C to +60°C
  - Storage temperature range: -40°C to +85°C
  - Dimension: 94mm x 65mm x 78.8mm
  - Weight: 360g
- 9" Waterproof Digital Wireless System