

SURFACE MOUNT SOCKETS & GAUGES

SINGLE PACK



LV1781W

WHITE DUAL SURFACE MOUNT
ACCESSORY SOCKET/
TWIN OUTPUT USB PORT



- Accessory socket x 1 & twin USB port x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- USB output: 5V/2.1A x 2
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 98(W) x 50(H) x 80(D)mm
- Cnt to cnt: 81.2mm
- Marine applications



LV1747

DUAL SURFACE MOUNT MERIT SOCKET/
VOLTMETER



- Merit socket x 1 & voltmeter x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- Voltmeter reading: 5-30V
- Red LED display
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 98(W) x 50(H) x 80(D)mm
- Cnt to cnt: 81.2mm



LV1746

DUAL SURFACE MOUNT MERIT SOCKET/
TWIN OUTPUT USB PORT



- Merit socket x 1 & twin USB port x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- USB output: 5V/2.1A x 2
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 98(W) x 50(H) x 80(D)mm
- Cnt to cnt: 81.2mm



LV1784

DUAL SURFACE MOUNT DIGITAL
VOLTMETER/TWIN OUTPUT USB PORT



- Voltmeter x 1 & twin USB port x 1
- Voltage: 12/24V
- Voltmeter reading: 5-30V
- Material: Thermoplastic Nylon 66
- Red LED display
- USB current output: 5V/2.1A x 2
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 98(W) x 50(H) x 80(D)mm
- Cnt to cnt: 81.2mm

