

## SHUTDOWN SOLENOIDS

SINGLE PACK/KIT

**Baxters**  
THE DRIVING FORCE IN AUTOMOTIVE SOLUTIONS

### BSS129412

#### 12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Coil terminals: 3 x prewired leads
- 2 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 46A, hold current: 1.1A
- Pull rating: 26 Lbs, hold rating: 35 Lbs
- Operating temperature: -40°C to +120°C
- Reference: 1756ES-12SUC5B1S5, 17520-60013, SA-5176-12



### BSSK3765-24

#### 24V RSV SHUTDOWN SOLENOID KIT LEFT HAND MOUNT



- Voltage: 24V
- Material: Metal housing
- Coil terminals: 2 x screw terminals
- Bolt left hand mounting
- Rated stroke: 38.6mm (1.5")
- Pull current: 46A, hold current: 1.1A
- Pull rating: 24 Lbs, hold rating: 38 Lbs
- Operating temperature: -40°C to +120°C
- Application: RSV Bosch
- Reference: SA-3765-24



### BSS112912

#### 12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Coil terminals: 3 x prewired leads
- 2 x bolt mounting
- Rated stroke: 25.4mm (1")
- Pull current: 62A, hold current: 0.9A
- Pull rating: 29 Lbs, hold rating: 41 Lbs
- Operating temperature: -40°C to +120°C
- Application: Cummins 6BT
- Reference: SA-4755-12



### BSS2003-12

#### 12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 4 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 60A, hold current: 1.7A
- Pull rating: 26 Lbs, hold rating: 51 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 63.5mm
- Reference: 2003-12E2U1B1S1A



### BSS1751-12

#### 12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 2 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 46A, hold current: 1.1A
- Pull rating: 24 Lbs, hold rating: 38 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 50.8mm
- Reference: 1751-12E2U1B1S1A



### BSS2003-24

#### 24V ENGINE SHUTDOWN SOLENOID



- Voltage: 24V
- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 4 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 31A, hold current: 0.8A
- Pull rating: 26 Lbs, hold rating: 51 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 63.5mm
- Reference: 2003-24E2U1B1S1A

