

Heatshrink

Heatshrink

- Flame retardant self extinguishing cross linked polyolefin
- Operating Temperature: -75°C to +135°C

Low VOLTAGE

Part No.	Pre Shrunk Dia.	Colour	Length
LV3300	3mm	Black	1.2m
LV3301		Black	400m
LV3302		Red	1.2m
LV3303		Red	400m
LV3304	5mm	Black	1.2m
LV3305		Black	200m
LV3306		Red	1.2m
LV3307		Red	200m
LV3308	7mm	Black	1.2m
LV3309		Black	100m
LV3310		Red	1.2m
LV3311		Red	100m
LV3312	10mm	Black	1.2m
LV3313		Black	100m
LV3314		Red	1.2m
LV3315		Red	100m
LV3316	13mm	Black	1.2m
LV3317		Black	100m
LV3318		Red	1.2m
LV3319		Red	100m
LV3320	19mm	Black	1.2m
LV3321		Black	100m
LV3322		Red	1.2m
LV3323		Red	100m
LV3324	25mm	Black	1.2m
LV3325		Black	50m
LV3326		Red	1.2m
LV3327		Red	50m



Dual Wall Heatshrink

- Flame retardant self extinguishing cross linked polyolefin
- Heavy Duty with an inner adhesive
- Operating Temperature: -55°C to +125°C

Low VOLTAGE

Part No.	Pre Shrunk Dia.	Colour	Length
LV3350	3mm	Black	1.2m
LV3350R		Red	
LV3351	4.8mm	Black	1.2m
LV3351R		Red	
LV3352	6mm	Black	1.2m
LV3352R		Red	
LV3353	9mm	Black	1.2m
LV3353R		Red	
LV3354	12mm	Black	1.2m
LV3354R		Red	
LV3355	18mm	Black	1.2m
LV3355R		Red	
LV3356	24mm	Black	1.2m
LV3356R		Red	
LV3357	39mm	Black	1.2m
LV3357R		Red	

