

CONTINUOUS DUTY SOLENOIDS

SINGLE PACK



LV5704

12V 80A CONTINUOUS DUTY SOLENOID
N/O CONTACTS



- Continuous Rating: 80A, SPST
- Material: Plated steel case
- Contacts: Silver
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 90mm




LV5703

12V 85A CONTINUOUS DUTY SOLENOID
N/O CONTACTS



- Continuous Rating: 85A, SPST
- Material: Plated steel case
- Contacts: Copper
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 90mm



LV5706

12V 150A CONTINUOUS DUTY SOLENOID
N/O CONTACTS



- Continuous Rating: 150A, SPST
- Material: Plated steel case
- Contacts: Silver
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C
- Cnt to cnt: 55mm
- Dimensions: 48 x 86 x 95mm




LV5705

24V 80A CONTINUOUS DUTY SOLENOID
N/O CONTACTS



- Continuous Rating: 80A, SPST
- Material: Plated steel case
- Contacts: Copper
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 90mm



LV5707

24V 100A CONTINUOUS DUTY SOLENOID
N/O CONTACTS



- Continuous Rating: 100A, SPST
- Material: Plated steel case
- Contacts: Silver
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C
- Cnt to cnt: 55mm
- Dimensions: 48 x 86 x 95mm

