

POWER PRODUCTS

Handbrake Alarm 12/24V

- A audible & visual alarm will be activated if a vehicles door is opened without the handbrake being applied.
- The alarm will only stop once the handbrake has been applied
- Suitable for positive and negative switched handbrake switches
- Can run an optional buzzer



Part No.	Input Voltage	Dimensions	Weight
LV1650	10-29V DC	62 x 36 x 21mm	260g



Low Water Level Alarm

- Low water level alarm has both audible & visual indicators.
- Warning Lamp illuminates as initial warning if coolant drops below level of sensing probe. If the coolant level remains below the sensing probe for 4 seconds or more the warning buzzer will be activated.
- Probes available for plastic or metal radiator tanks (sold separately)
- Can be used in conjunction with a relay to activate a horn or a fuel cut/off system. (Relay not supplied)
- Suitable for water based fluids only. Not suitable for oil or petroleum products.
- Suits negative earth systems



Part No.	Input Voltage	Operating Current	Dimensions
LV1600	11-14V DC	13mA	86 x 66 x 30mm
LV1601	22-28V DC	15mA	86 x 66 x 30mm



Probes to suit:	Part No.	Description
	LV1605	Probe to suit radiators with plastic tanks
	LV1606	Probe to suit radiators with metal tanks

