

## MANUAL RESET PANEL MOUNT CIRCUIT BREAKERS MID-RANGE TYPE


- Voltage: up to 32V
- Current rating: 10 - 50A
- Housing material: Black UL-rated 94V0 thermoset plastic body
- Stud size: #10-32 external thread
- Interrupt capacity: 2500A@30Vdc
- Operating temperature: -40°C to 80°C
- Ignition protected: SAE J1171
- Testing: SAE J553; ABYC E-11
- Mounting hole: \#8-32 with threaded inserts
- IP rating: IP67
- Marine & Mining applications



**Bussmann**



**SINGLE PACK**



**PRODUCT INFORMATION**

Part No.	Amperage	Part No.	Amperage
LV4712	10A	LV4716	30A
LV4713	15A	LV4717	35A
LV4714	20A	LV4718	40A
LV4715	25A	LV4719	50A

## MANUAL RESET PANEL MOUNT CIRCUIT BREAKERS


- Input voltage: up to 30Vdc
- Current rating: 6 - 40A
- Housing: Thermoplastic
- Operating temperature: -51°C to +71°C
- Includes mounting nut inserts
- Cnt to cnt: 40mm
- Termination: Screw 8-32 UNC
- Dielectric strength: >1500Vac/Min.
- Insulation resistance: >100MOhm (500Vdc)
- Ignition protected
- UL Recognized E36869
- Marine & Mining applications



**KLIXON**



**SINGLE PACK**



**PRODUCT INFORMATION**

Part No.	Amperage	Part No.	Amperage
CDM5I	5A	CDM20I	20A
CDM10I	10A	CDM30I	30A
CDM15I	15A	CDM40I	40A

## MANUAL RESET PANEL MOUNT CIRCUIT BREAKERS


- Input voltage: up to 30Vdc
- Current rating: 50 - 150A
- Housing: Thermoplastic
- Operating temperature: -51°C to +71°C
- Includes mounting nut inserts
- Cnt to cnt: 60.9mm
- Termination: Screw 1/4-28 UNF-2A
- Dielectric strength: >1500Vac/Min.
- Insulation resistance: >100MOhm (500Vdc)
- Ignition protected
- UL Recognized E69772
- Marine & Mining applications



**KLIXON**



**SINGLE PACK**



**PRODUCT INFORMATION**

Part No.	Amperage	Part No.	Amperage
SDLM50I	50A	SDLM105I	105A
SDLM60I	60A	SDLM120I	120A
SDLM80I	80A	SDLM150I	150A