

CONTINUOUS DUTY SOLENOIDS

SINGLE PACK


CH Cole Hersee
A Littelfuse Brand

24401BX

12V 85A CONTINUOUS DUTY SOLENOID CHANGE OVER CONTACTS



- Continuous Rating: 85A, DPST 2 Circuit
- Material: Plated steel case
- Contacts: Copper
- Battery studs: 4 x copper stud (5/16" - 24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 70 x 84mm




24402BX

24V 85A CONTINUOUS DUTY SOLENOID CHANGE OVER CONTACTS



- Continuous Rating: 85A, DPST 2 Circuit
- Material: Plated steel case
- Contacts: Copper
- Battery studs: 4 x copper stud (5/16" - 24)
- Coil studs: 2 x copper stud (10-32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 70 x 84mm




24512-10BX

12V 100A CONTINUOUS DUTY SOLENOID N/O CONTACTS



- Continuous Rating: 100A/400A - 10 Sec, SPST
- Material: Glass nylon housing
- Contacts: Silver
- Battery Studs: 2 x copper stud (5/16" - 24)
- Coil studs: 2 x blade terminals
- Operating temperature: -40°C to +60°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 65 x 47 x 76mm




24612-10BX

12V 100A CONTINUOUS DUTY SOLENOID N/O CONTACTS



- Continuous Rating: 100A/400A - 10 Sec, SPST
- Material: Glass nylon housing
- Contacts: Silver
- Battery Studs: 2 x copper stud (5/16" - 24)
- Coil studs: 2 x stud terminals (10 - 32)
- Operating temperature: -40°C to +60°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 65 x 47 x 76mm



24624-10BX

24V 100A CONTINUOUS DUTY SOLENOID N/O CONTACTS



- Continuous Rating: 100A/200A - 10 Sec, SPST
- Material: Glass nylon housing
- Contacts: Silver
- Battery Studs: 2 x copper stud (5/16"-24)
- Coil studs: 2 x stud terminals (10-32)
- Operating temperature: -40°C to +60°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 65 x 47 x 76mm

