

# BRD281 SERIES

# ROADVISION



## FEATURES

- Stop/Tail Indicator or Stop/Tail Indicator & Reverse functions
- Sequential Indicator
- Dynamic start up Grey Glowtech tail light
- Integrated Retro Reflector
- Multi-volt 10-30V DC input & low current draw
- 100,000HR rated LED lifespan with solid state technology
- Simple surface mount design
- ADR approved for all functions
- Light weight tough polycarbonate housing & lens
- Mild tinted lens and gun metal grey chrome finish

## LED COMBINATION LAMPS



Upgrade your vehicle's rear lighting with the ROADVISION BRD281 Series—where cutting-edge design meets uncompromising performance. Featuring Stop/Tail/Indicator or Stop/Tail/Indicator & Reverse functions, the BRD281 Series is equipped with a sleek sequential indicator and **dynamic start up Grey Glowtech** tail light for a distinctive look and enhanced road presence. The integrated retro reflector boosts visibility, while multi-volt 10–30V DC input and low current draw ensure energy-efficient operation. Designed for durability with a lightweight, tough polycarbonate housing and lens, these lamps are ADR approved for all functions and built to last with a 100,000-hour rated solid-state LED lifespan. A mild tinted lens and gun metal grey chrome finish complete the look, making the BRD281 Series the ultimate blend of style, safety, and reliability.

### PART NUMBERS

**BRD281ARR**  
LED Rear Combination Lamp 10-30V Stop/Tail/Ind/Ref  
200x100x37mm Dynamic Glow Tail

### PART NUMBERS

**BRD281ARW**  
LED Rear Combination Lamp 10-30V Stop/Tail/Ind/Rev/Ref  
200x100x37mm Dynamic Glow Tail

SPECIFICATIONS	BRD281ARR	BRD281ARW
INPUT VOLTAGE	10-30 VDC	10-30 VDC
NUMBER OF LEDs	Indicator - 15 LEDs, Stop - 48 LEDs, Tail - 36 LEDs	Indicator - 15 LEDs, Stop - 32 LEDs, Tail - 36 LEDs, Reverse - 16 LEDs
CURRENT DRAW @ 13.8V	Ind - 0.29A, Stop - 0.33A, Tail - 0.14A @ 13.8V	Ind - 0.29A, Stop - 0.2A, Tail - 0.14A, Rev - 0.26A @ 13.8V
LENS CONSTRUCTION	Polycarbonate	Polycarbonate
HOUSING CONSTRUCTION	Polycarbonate	Polycarbonate
MOUNTING HOLE CENTRES	120mm	120mm
OVERALL DIMENSIONS	280 x 100 x 37mm	280 x 100 x 37mm
CABLE LENGTH	300mm Tinned Copper	300mm Tinned Copper
CTA APPROVAL	CTA-061834	CTA-061825
WIRING	Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow	Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow, Reverse - Black

### LINE DIAGRAM

