


DUAL WALL HEATSHRINK IN 1.2M LENGTH

- Material: Polyolefin
- Ratio: 3:1
- Breakdown voltage: 600V
- Operating temperature: -55°C to +125°C
- UL VW-1 & CSA: flame retardant, self extinguishing
- Pack in cut length



CUT LENGTH



PRODUCT INFORMATION


Part No.	Inside Dia.	Colour	Length	Part No.	Inside Dia.	Colour	Length
LV3350	3mm	Black	1.2m	LV3355R	19mm	Red	1.2m
LV3350R	3mm	Red	1.2m	LV3356	25.4mm	Black	1.2m
LV3351	4.8mm	Black	1.2m	LV3356R	25.4mm	Red	1.2m
LV3351R	4.8mm	Red	1.2m	LV3357	39mm	Black	1.2m
LV3352	6.4mm	Black	1.2m	LV3357R	39mm	Red	1.2m
LV3352R	6.4mm	Red	1.2m	LV3395	50mm	Black	1.2m
LV3353	9.5mm	Black	1.2m	LV3395R	50mm	Red	1.2m
LV3353R	9.5mm	Red	1.2m	LV3396	64mm	Black	1.2m
LV3354	12.7mm	Black	1.2m	LV3396R	64mm	Red	1.2m
LV3354R	12.7mm	Red	1.2m	LV3397	76mm	Black	1.2m
LV3355	19mm	Black	1.2m	LV3397R	76mm	Red	1.2m

DUAL WALL HEATSHRINK IN SPOOL

- Material: Polyolefin
- Ratio: 3:1
- Breakdown voltage: 600V
- Operating temperature: -55°C to +125°C
- UL VW-1 & CSA: flame retardant, self extinguishing
- Pack in spool



SPOOL



PRODUCT INFORMATION

Part No.	Inside Dia.	Colour	Length
LV3354/25M	12.7mm	Black	25m
LV3354R/25M	12.7mm	Red	25m
LV3355/25M	19mm	Black	25m
LV3355R/25M	19mm	Red	25m