


ANL FUSE

- Voltage: up to 32/80V
- Interrupting rating: 2000A @32V
- Interrupting rating: 2000A @80V (300A - 500A)
- Medium time lag
- Material: Gold plated copper alloy/Bakerlite (35A -200A)
- Material: Gold plated copper alloy/ceramic (250A -500A)
- Operating temperature: -40°C to 125°C
- Mounting hole: Ø8.5mm (elongated)
- Complies with ISO 8820-5



SINGLE PACK



PRODUCT INFORMATION


Single Pack	Amperage	Single Pack	Amperage	Single Pack	Amperage
LV5300	35A	LV5305	125A	LV5310	300A
LV5301	50A	LV5306	150A	LV5311	355A
LV5302	60A	LV5307	175A	LV5312	400A
LV5303	80A	LV5308	200A	LV5313	425A
LV5304	100A	LV5309	250A	LV5314	500A

MARINE RATED BATTERY FUSE (MRBF)

- Voltage: up to 58V
- Interrupting rating: 2000A@58Vdc
- Materials: Copper alloy/ ceramic/ plastic
- Operating temperature: -40°C to 125°C
- Ignition protected
- Complies with ISO 8820-6
- Fuse holder to suit: **LV5511**, refer to page 235



SINGLE PACK



PRODUCT INFORMATION


Single Pack	Amperage	Colour	Single Pack	Amperage	Colour
LV5500	100A	Yellow	LV5504	200A	Blue
LV5501	125A	Green	LV5505	250A	Pink
LV5502	150A	Orange	LV5506	300A	Grey
LV5503	175A	White			

M-CASE SLOTTED FUSIBLE LINK

- Voltage: up to 58Vdc
- Breaking capacity: 1000A@58Vdc
- Slotted terminal design
- 6.3mm Slot
- Busbar power feed
- Slow blow Fuses
- Operating temperature: -40°C to 125°C
- Terminal: Copper alloy
- Plastic body



PACK OF 10



PRODUCT INFORMATION

10 Pack	Amperage	Housing Colour	10 Pack	Amperage	Housing Colour
LV5513	15A	Grey	LV5517	40A	Green
LV5514	20A	Blue	LV5518	50A	Red
LV5515	25A	White	LV5519	60A	Yellow
LV5516	30A	Pink			