


SENSOR / BATTERY MASTER SWITCH ACCESSORIES

PACK OF 1/10

RS400 ROLL OVER STABILITY SENSOR



- Voltage: 9 - 32VDC
- Operating temp.: -20°C to 60°C
- Contact current rating: 10A DC switching current (NOHP to 0V); 0.15A
- DC Switching Current (NO/NC to COM) Standards: Meets AS2809-2008
- IP rating: IP66
- Dimensions: 184[L] x 114[W] x 61[H]mm
- Weight: 2.2kg
- Compatible with DPS & TSW switches



VRD12-24 ROLL OVER STABILITY SENSOR



- Voltage: 10 - 30VDC
- Operating temp.: -20°C to 60°C
- Standards: AS2809
- Dimensions: 105 x 90 x 55mm
- Compatible with DPS & TSW switches



LV5005 M10 TERMINAL EXTENSION STUD



- M10 Terminal extension stud
- Overall length 59mm
- Solid brass 19mm spanner
- Thread size: M10 x 1.5
- Single blister pack



LV5006 3/8" TERMINAL EXTENSION STUD



- 3/8" Terminal extension stud
- Overall length 59mm
- Solid brass 19mm spanner
- Thread size: 3/8" - 24
- Single blister pack



* Commonly used on Cole Hersee Battery Master Switches

LV5007R BATTERY ISOLATOR LABELS

PACK OF 10



- Adhesive backing
- Outdoor reflective vinyl sticker
- Weatherproof
- Visible in the dark
- Trimmed to size
- Dimensions: 60 x 30mm
- Pack of 10



LV5007Y STARTER ISOLATOR LABELS

PACK OF 10



- Adhesive backing
- Outdoor reflective vinyl sticker
- Weatherproof
- Visible in the dark
- Trimmed to size
- Dimensions: 60 x 30mm
- Pack of 10



LV5049-KEY REPLACEMENT RED KEY



- Replacement key for LV5049



LV4951-KEY REPLACEMENT RED KEY



- Replacement key for LV4951

