

EMERGENCY STOP SWITCHES

SINGLE PACK

LV5013

NC/NC 12/24V E-STOP SWITCH
LATCHING TWIST TO RESET



- Housing material: Polyamide with glass fibre
- Voltage range: 9Vdc to 32Vdc
- Nominal voltage: 12/24Vdc
- Contact: 2 x N/C
- Contact material: Silver alloy
- Latching/twist to reset
- Contact rating: 8A cont.
- Panel hole: Ø30.5mm
- Switch connection type: Deutsch DT04-4P
- Cable length: 200mm
- Mushroom head: Ø40mm
- IP rating: IP6K9K
- Use legend: **LV5029**



KES0312

C/O 12/24V E-STOP SWITCH
LATCHING TWIST TO RESET



- Housing material: Polyamide with glass fibre
- Voltage range: 9Vdc to 32Vdc
- Nominal voltage: 12/24Vdc
- Contacts: 2 x C/O
- Contact material: Silver alloy
- Latching/twist to reset
- Contact rating: 8A cont.
- Panel hole: Ø30.5mm
- Mating connector supplied
- Cable length: 200mm
- Mushroom head: Ø40mm
- IP rating: IP6K9K
- Use legend: **KES0023**



KES0412

NO/NC 12/24V E-STOP SWITCH
LATCHING TWIST TO RESET



- Housing material: Polyamide with glass fibre
- Voltage range: 9Vdc to 32Vdc
- Nominal voltage: 12/24Vdc
- Contacts: 1 x N/O, 1 x N/C
- Contact material: Silver alloy
- Latching/twist to reset
- Contact rating: 8A cont.
- Panel hole: Ø30.5mm
- Mating connector supplied
- Right angle/lateral cable exit
- Cable length: 200mm
- Mushroom head: Ø40mm
- IP rating: IP6K9K
- Use legend: **KES0023**



KES0311

C/O 12/24V E-STOP SWITCH
LATCHING TWIST TO RESET



- Housing material: Polyamide with glass fibre
- Voltage range: 9Vdc to 32Vdc
- Nominal voltage: 12/24Vdc
- Contacts: 2 x C/O
- Contact material: Silver alloy
- Latching/twist to reset
- Contact rating: 8A cont.
- Panel hole: Ø30.5mm
- Mating connector supplied
- Cable length: 200mm
- Mushroom head: Ø30mm
- IP rating: IP6K9K
- Use legend: **KES0023**

