

## 90° CABLE LUGS

- For flexible & stranded cables
- Electrolytic copper 99.95% purity
- Annealed material to ensure optimal crimping properties
- Tin plated surface 5 - 10 microns
- Internal chamfer for easy cable insertion
- Operating temperature: -55°C to 155°C



BAG



### PRODUCT INFORMATION

Part No.	Description	Industry Ref.	Cable Size	B & S Equivalent	Stud Size	Qty
LV4157	Cable lug - 90°	10-6	10mm <sup>2</sup>	8 B&S	6mm	10
LV4158	Cable lug - 90°	10-8	10mm <sup>2</sup>	8 B&S	8mm	10
LV4159	Cable lug - 90°	16-6	16mm <sup>2</sup>	6 B&S	6mm	10
LV4160	Cable lug - 90°	16-8	16mm <sup>2</sup>	6 B&S	8mm	10
LV4161	Cable lug - 90°	16-10	16mm <sup>2</sup>	6 B&S	10mm	10
LV4162	Cable lug - 90°	25-8	25mm <sup>2</sup>	3 B&S	8mm	10
LV4163	Cable lug - 90°	25-10	25mm <sup>2</sup>	3 B&S	10mm	10
LV4174	Cable lug - 90°	35-8	35mm <sup>2</sup>	2 B&S	8mm	10
LV4175	Cable lug - 90°	35-10	35mm <sup>2</sup>	2 B&S	10mm	10
LV4164	Cable lug - 90°	50-8	50mm <sup>2</sup>	0 B&S	8mm	10
LV4165	Cable lug - 90°	50-10	50mm <sup>2</sup>	0 B&S	10mm	10
LV4166	Cable lug - 90°	70-8	70mm <sup>2</sup>	00 B&S	8mm	10
LV4167	Cable lug - 90°	70-10	70mm <sup>2</sup>	00 B&S	10mm	10
LV4168	Cable lug - 90°	70-12	70mm <sup>2</sup>	00 B&S	12mm	10
LV4169	Cable lug - 90°	95-8	95mm <sup>2</sup>	000 B&S	8mm	10
LV4170	Cable lug - 90°	95-10	95mm <sup>2</sup>	000 B&S	10mm	10
LV4171	Cable lug - 90°	95-12	95mm <sup>2</sup>	000 B&S	12mm	10
LV4172	Cable lug - 90°	120-10	120mm <sup>2</sup>	0000 B&S	10mm	5
LV4173	Cable lug - 90°	120-12	120mm <sup>2</sup>	0000 B&S	12mm	5