

BATTERY MASTER SWITCHES

SINGLE PACK

BMS514Y BATTERY MASTER SWITCH




- Voltage: 0 - 32V
- Amperage: 500A cont. ; 2500A/10 secs. ; 2000A/75 secs.
- Type: SPST Battery
- In-built lock-out
- Operating temperature: -40°C to +85°C
- Silver contacts
- Mounting ctn to ctn: 100mm
- Mounting hole cut out: Ø70mm
- Mounting hole: Ø8.5mm
- Stud size: M12 x 4
- IP rating: IP67
- Kissling



880175 LOCKABLE BLACK DUAL POLE MASTER DISCONNECT SWITCH



- Max continuous current: 500A per circuit, with 2 x 4/0 input & 2 x 4/0 output cables
- 350A per circuit, with 1 x 4/0 input & 1 x 4/0 output cables
- Intermittent rating (30 sec): 2,250A per circuit with 2 x 4/0 input and 2 x 4/0 output cables. 1,750A per circuit with 1 x 4/0 input and 1 x 4/0 output cables
- DPST
- Operating temperature: -50°C to +85°C, DC-rated to 105°C
- Stud size: M12x25mm
- IP rating: IP67/IP69K



880175-0001 LOCKABLE RED DUAL POLE MASTER DISCONNECT SWITCH



- Max continuous current: 500A per circuit, with 2 x 4/0 input & 2 x 4/0 output cables
- 350A per circuit, with 1 x 4/0 input & 1 x 4/0 output cables
- Intermittent rating (30 sec): 2,250A per circuit with 2 x 4/0 input and 2 x 4/0 output cables. 1,750A per circuit with 1 x 4/0 input and 1 x 4/0 output cables
- DPST
- Operating temperature: -50°C to +85°C, DC-rated to 105°C
- Stud size: M12x25mm
- IP rating: IP67/IP69K



880175-0002 LOCKABLE YELLOW DUAL POLE MASTER DISCONNECT SWITCH



- Max continuous current: 500A per circuit, with 2 x 4/0 input & 2 x 4/0 output cables
- 350A per circuit, with 1 x 4/0 input & 1 x 4/0 output cables
- Intermittent rating (30 sec): 2,250A per circuit with 2 x 4/0 input and 2 x 4/0 output cables. 1,750A per circuit with 1 x 4/0 input and 1 x 4/0 output cables
- DPST
- Operating temperature: -50°C to +85°C, DC-rated to 105°C
- Stud size: M12x25mm
- IP rating: IP67/IP69K



75920BX INTEGRATED LOCKABLE RED HANDLE BATTERY MASTER SWITCH



- Heavy Duty
- Amperage: 300A cont., 1000A to 3000A Intermittent
- Material: ABS body, silver contacts
- Battery: 2 x 3/8"
- Stem: Ø3/4"-16, O'Ring sealed
- Stem: panel thickness: 12mm
- Dimensions: 69 (D) x 136mm Max (H)
- IP rating: IP67



75920-01BX INTEGRATED LOCKABLE YELLOW HANDLE BATTERY MASTER SWITCH



- Heavy Duty
- Amperage: 300A cont., 1000A to 3000A Intermittent
- Material: ABS body, silver contacts
- Battery: 2 x 3/8"
- Stem: Ø3/4"-16, O'Ring sealed
- Stem: panel thickness: 12mm
- Dimensions: 69 (D) x 136mm Max (H)
- IP rating: IP67

