



TWO CORE TWIN SHEATH BATTERY CABLE

ROLL

- Conductor: Oxygen free plain copper wire to AS/NZS 1125
- Insulation: V90 PVC to AS/NZS3808
- Voltage: 50Vac or 120Vdc
- Applications: Battery feeds, chargers, winches, power & solar generators
- Insulation thickness: 8B&S/0.9mm; 6/4B&S/1.1mm
- Sheath colour: Black/Red Stripe
- Core colour: Black & Red



PRODUCT INFORMATION

Part No.	Size (B&S)	Area (mm ²)	Amp@30°C	Length (m)	Strands/Dia.	Resistance@20°C (Ohm/km)	O.D (mm)	Mass (kg/100m)
CB108A2-030BKRD	8	7.71	59.2	30	96/0.32	2.4	7.1x12.5	22
CB108A2-050BKRD	8	7.71	59.2	50	96/0.32	2.4	7.1x12.5	22
CB108A2-100BKRD	8	7.71	59.2	100	96/0.32	2.4	7.1x12.5	22
CB106A2-050BKRD	6	13.5	82.4	50	168/0.32	1.4	8.8x16	36
CB106A2-100BKRD	6	13.5	82.4	100	168/0.32	1.4	8.8x16	36
CB104A2-030BKRD	4	20.26	108	30	252/0.32	1	10.3x18.6	52.2

TWO CORE CLEAR SHEATH BATTERY CABLE

- Conductor: Nominal 0.2mm Oxygen free plain copper wire to AS/NZS 1125
- Insulation: V90 PVC to AS/NZS3808
- Voltage: up to 450V
- Applications: Motorised vehicles, forklifts, field conveyor, booster cables
- Sheath: UV Stabilised PVC type rated V90 to AS/NZS3808
- Sheath colour: Clear
- Core colour: Black & Red
- Sheath thickness: 0.9mm



PRODUCT INFORMATION

Part No.	Area (mm ²)	Amp@30°C	Length (m)	Strands/Dia.	Resistance@20°C (Ohm/km)	O.D (mm)	Mass (kg/100m)
CB010E2-050RDBK	10	74	50	322/0.2	1.91	8x17	16.5