




## 4MM SINGLE CORE CABLE WITH TRACE

ROLL

- Conductor: Oxygen free plain copper wire to AS/NZS 1125
- Insulation: V90 PVC to AS/NZS3808
- Voltage: 50Vac or 120Vdc
- Applications: General purpose automotive wiring
- Conductor: 23 Strands x Ø0.32mm
- Nominal area: 1.84mm<sup>2</sup>
- Current rating: 28A@30°C
- Insulation thickness: 0.4mm
- Resistance@20°C: 10.10hm/km
- Nominal O.D: 2.6mm
- Mass: 2.1Kg/100m



### PRODUCT INFORMATION

Part No.	Colour	Length(m)	Part No.	Colour	Length(m)
CB004A1-030BEWE	Blue/White trace	30	CB004A1-030GNWE	Green/White trace	30
CB004A1-100BEWE	Blue/White trace	100	CB004A1-100GNWE	Green/White trace	100
CB004A1-030BKGN	Black/Green trace	30	CB004A1-100GYBN	Grey/Brown trace	100
CB004A1-100BKGN	Black/Green trace	100	CB004A1-030OEBE	Orange/Blue trace	30
CB004A1-030BKWE	Black/White trace	30	CB004A1-100PKBE	Pink/Blue trace	100
CB004A1-100BKWE	Black/White trace	100	CB004A1-100PKBK	Pink/Black trace	100
CB004A1-030BKYW	Black/Yellow trace	30	CB004A1-030RDBE	Red/Blue trace	30
CB004A1-100BKYW	Black/Yellow trace	100	CB004A1-100RDBE	Red/Blue trace	100
CB004A1-030BNBE	Brown/Blue trace	30	CB004A1-030RDBK	Red/Black trace	30
CB004A1-100BNGN	Brown/Green trace	100	CB004A1-100RDBK	Red/Black trace	100
CB004A1-030BNWE	Brown/White trace	30	CB004A1-030RDWE	Red/White trace	30
CB004A1-100BNWE	Brown/White trace	100	CB004A1-100RDWE	Red/White trace	100
CB004A1-030GNBK	Green/Black trace	30	CB004A1-100WEBK	White/Black trace	100
CB004A1-100GNBK	Green/Black trace	100	CB004A1-030WEBN	White/Brown trace	30
CB004A1-030GNRD	Green/Red trace	30	CB004A1-030YWBE	Yellow/Blue trace	30
CB004A1-100GNRD	Green/Red trace	100	CB004A1-100YWBE	Yellow/Blue trace	100
CB004A1-030GNVT	Green/Violet trace	30	CB004A1-030YWBK	Yellow/Black trace	30