


# Micro Switches

## E52-3500

### Micro Switch


- Micro Switch - Pin Push Button
- Temperature Range  $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- Completely Sealed Construction
- OF Max: 250 - 450g
- RF Min: 114g
- PT Max: 0.5mm
- OT Min: 0.13mm
- DT Max: 0.05mm
- OP:  $15.9 \pm 0.4\text{mm}$



## E52-3501

### Micro Switch


- Micro Switch - Med Pin Push Button
- Temperature Range  $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- OF Max: 250 - 450g
- RF Min: 114g
- PT Max: 0.5mm
- OT Min: 1.6mm
- DT Max: 0.05mm
- OP:  $28.2 \pm 0.5\text{mm}$



## E52-3502

### Micro Switch


- Micro Switch - Med Push Button
- Temperature Range  $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- OF Max: 250 - 450g
- RF Min: 114g
- PT Max: 0.5mm
- OT Min: 1.6mm
- DT Max: 0.05mm
- OP:  $21.5 \pm 0.5\text{mm}$



## E52-3503

### Micro Switch


- Micro Switch - Large Push Button Nut
- Temperature Range  $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- OF Max: 250 - 450g
- RF Min: 114g
- PT Max: 0.5mm
- OT Min: 5.5mm
- DT Max: 0.05mm
- OP:  $38.1 \pm 0.8\text{mm}$



## E52-3504

### Micro Switch

- Micro Switch - Push Roller Nut Straight
- Temperature Range  $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- OF Max: 250 - 450g
- RF Min: 114g
- PT Max: 0.5mm
- OT Min: 3.58mm
- DT Max: 0.05mm
- OP:  $49.7 \pm 1.2\text{mm}$



## E52-3505

### Micro Switch

- Micro Switch - Push Roller Nut Right
- Temperature Range  $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- OF Max: 250 - 450g
- RF Min: 114g
- PT Max: 0.5mm
- OT Min: 3.58mm
- DT Max: 0.05mm
- OP:  $49.7 \pm 1.2\text{mm}$

