


ULTRARAY®

■ Amber Illuminated - Direct Mount	HM400ADIR
■ Amber Illuminated - Magnetic Mount	HM400AMAG
■ Red Illuminated - Direct Mount	HM400RDIR
■ Red Illuminated - Magnetic Mount	HM400RMAG
■ Blue Illuminated - Direct Mount	HM400BDIR
■ Blue Illuminated - Magnetic Mount	HM400BMAG
■ Green Illuminated - Direct Mount	HM400GDIR
■ Green Illuminated - Magnetic Mount	HM400GMAG
■ White Illuminated - Direct Mount	HM400WDIR
■ White Illuminated - Magnetic Mount	HM400WMAG



Extremely robust LED Warning Beacon for heavy-duty applications, featuring four user-selectable flash patterns and automatic daylight detection to suit a large variety of applications. Equipped with high-impact resistant, clear polycarbonate lens bolted to a heavy-duty, corrosion-resistant cast-alloy base. O-ring sealed against dust and water ingress.

<b>Voltage</b>	Multivolt™ (12-30V DC)	
<b>Wattage</b>	20W Max.	
<b>Flash Rate</b>	80 per minute (double). 4 user-selectable flash patterns (double, quad and 2 random patterns).	
<b>Temp. Range</b>	-20° to +50°C	
<b>Mounting</b>	Fixed or magnetic mounting on horizontal surfaces. Optional pipe mount kit available.	
<b>Lead Length</b>	2 metres (double-insulated cable).	
<b>Protection</b>	Overheat, reverse polarity and short circuit protected. Fully sealed against dust and moisture to IP6K5. Shock resistant to 200G.	
<b>Note</b>	Meets SAE J845 requirements for Class 1 (red and amber)	
<b>Accessories</b>	HM400PIPE 9.HM450FLX	Pipe Mount Kit ① FlexiMount Adapter
<b>Spare Parts</b>	9.HM400LENS	Clear PC Lens