

QUICK CONNECTORS

BAG




- Housing material: Plastic
- Brass terminals
- Current rating: 15A
- Cable range: 0.5 - 2.0mm²

- Temperature range: -30°C to 105°C
- Interlock housings
- QC250 Series

QUICK CONNECTOR WHITE HOUSINGS

- Terminals included



PRODUCT INFORMATION

Part No.	Position	Description	Qty
LV2775	1 Way	Plug Housing	10
LV2776	1 Way	Socket Housing	10
LV2777	2 Way	Plug Housing	10
LV2778	2 Way	Socket Housing	10
LV2779	3 Way	Plug Housing	10
LV2780	3 Way	Socket Housing	10

Part No.	Position	Description	Qty
LV2781	4 Way	Plug Housing	10
LV2782	4 Way	Socket Housing	10
LV2783	6 Way	Plug Housing	10
LV2784	6 Way	Socket Housing	10
LV2785	8 Way	Plug Housing	10
LV2786	8 Way	Socket Housing	10


PRODUCT INFORMATION

Part No.	Position	Description	Qty
LV2775-100	1 Way	Plug Housing	100
LV2776-100	1 Way	Socket Housing	100
LV2777-100	2 Way	Plug Housing	100
LV2778-100	2 Way	Socket Housing	100

Part No.	Position	Description	Qty
LV2779-100	3 Way	Plug Housing	100
LV2780-100	3 Way	Socket Housing	100
LV2781-100	4 Way	Plug Housing	100
LV2782-100	4 Way	Socket Housing	100

QUICK CONNECTOR BLACK HOUSINGS

- Terminals included



PRODUCT INFORMATION

Part No.	Position	Description	Qty
LV2775-BK	1 Way	Plug Housing	10
LV2776-BK	1 Way	Socket Housing	10
LV2777-BK	2 Way	Plug Housing	10
LV2778-BK	2 Way	Socket Housing	10
LV2779-BK	3 Way	Plug Housing	10
LV2780-BK	3 Way	Socket Housing	10

Part No.	Position	Description	Qty
LV2781-BK	4 Way	Plug Housing	10
LV2782-BK	4 Way	Socket Housing	10
LV2783-BK	6 Way	Plug Housing	10
LV2784-BK	6 Way	Socket Housing	10
LV2785-BK	8 Way	Plug Housing	10
LV2786-BK	8 Way	Socket Housing	10

QUICK CONNECTOR TERMINALS

- Non insulated brass terminals
- Current rating: 15A
- Cable range: 0.5 - 2.0mm²

- Tab size: 6.3 x 0.8mm
- Temperature range: -30°C to 105°C

PRODUCT INFORMATION

Part No.	Description	Suits	Qty
LV2721	Male Blade Terminal	Socket Housing	100
LV2732	Female Blade Terminal	Plug Housing	100

