


## SPLIT WRAP BRAIDED SLEEVING IN SPOOL

- Material: PET monofilament
- Melting point: 250°C ± 5°C
- Operating temperature: -50°C to +150°C
- The 25% edge overlap (at nominal dia.)
- Cutting tool: Hot knife
- Certificate: RoHS, halogen free
- Flammability: VW-1
- Colour: Black
- Pack in spool



**SPOOL**



Overlap 25%



### PRODUCT INFORMATION

Part No.	Dia.	Length
LV3130	6mm	50m
LV3131	9mm	50m
LV3132	13mm	50m
LV3133	16mm	50m
LV3134	19mm	25m

Part No.	Inside Dia.	Length
LV3135	25mm	25m
LV3136	32mm	25m
LV3137	38mm	25m
LV3138	50mm	25m

## FABRIC HEATSHRINK WOVEN SLEEVE

- Fabric heatshrink woven sleeve
- Superior flexibility & abrasion resistant
- Shrink ratio: 2:1
- Operating temperature: -45°C to +125°C
- Full recovery: 110°C
- Certificate: UL, RoHS
- Colour: Black



**CUT LENGTH**



### PRODUCT INFORMATION

Part No.	Dia.	Length
LV3380	12mm	1.2m
LV3381	20mm	1.2m
LV3382	30mm	1.2m
LV3383	40mm	1.2m