

SHUTDOWN SOLENOIDS

SINGLE PACK/KIT

Baxters
THE DRIVING FORCE IN AUTOMOTIVE SOLUTIONS

BSS149112 12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Termination: 6.3mm blade terminal
- Mounting bracket: Flat mount
- Mounting hole Ø: 2 x 9.2mm elongated
- Applications: Various Kubota models
- Reference: 052600-1000, 15471-60010



BSS150012 12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Coil terminals: 3 x prewired leads
- 2 Bolt mounting bracket
- Pull current: 30A, hold current: 0.7A
- Operating temperature: -40°C to +120°C
- Application: Kubota, Yanmar, John Deere
- Reference: 1503ES-12S5SUC5S, SA-4562-T, 129486-77952



BSS129312 12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Coil terminals: 3 x prewired leads
- 2 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 46A, hold current: 1.1A
- Pull rating: 26 Lbs, hold rating: 35 Lbs
- Operating temperature: -40°C to +120°C
- Reference: SA-4899-12, 1756ES-12SULB1S5



BSS1943 24V ENGINE SHUTDOWN SOLENOID



- Voltage: 24V
- Material: Metal housing
- Coil terminals: 3 x prewired leads
- 2 x bolt mounting
- Rated stroke: 25.4mm (1")
- Pull current: 39A, hold current: 0.5A
- Pull rating: 29 Lbs, hold rating: 41 Lbs
- Operating temperature: -40°C to +120°C
- Application: Cummins
- Reference: 5346207, 5301701, 4942879, 5295567, 5292297



BSS425912 12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 2 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 46A, hold current: 1.1A
- Pull rating: 24 Lbs, hold rating: 38 Lbs
- Operating temperature: -40°C to +120°C
- Application: Kubota 70 & 802mm Series
- Cnt to cnt: 63.5mm
- Reference: 1751-12A6U1B1S5A



BSS1503ES-12S 12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Coil terminals: 3 x prewired leads
- 2 Bolt mounting bracket
- Rated stroke: 11mm
- Pull current: 29A, hold current: 0.38A
- Operating temperature: -40°C to +120°C
- Application: Kubota
- Reference: 1503ES-12S5SUC12S, 119233-77932

