

HEAT SHRINKABLE FULLY INSULATED PUSH ON TERMINALS



- Terminal material: Copper
- Insulation material: Polyethylene (PE)
- Heatshrink ratio: 3:1
- Shrink temperature: +150°C
- Operating temperature: -10°C to +105°C
- Double crimp

BOX



PRODUCT INFORMATION

Part No.	Colour	Wire Size	W x D x L	Qty	Packaging
LV2830	Red	2.5 - 3mm	6.3 x 6.5 x 28.0mm	50	Box
LV2831	Blue	4mm	6.3 x 6.5 x 28.0mm	50	Box
LV2832	Yellow	5 - 6mm	6.3 x 7.5 x 28.0mm	25	Box

HEAT SHRINKABLE MALE BULLET TERMINALS



- Material: Brass with copper sleeve
- High-density polyethylene (HDPE)
- Shrink temperature: +150 °C
- Operating temperature: - 40°C to + 105°C
- Max. voltage: 300V
- Double crimp

BOX



PRODUCT INFORMATION

Part No.	Colour	Wire Size	Tab Size	Qty	Packaging
LV2810	Red	2.5 - 3mm	4mm	50	Box
LV2811	Blue	4mm	5mm	50	Box
LV2812	Yellow	5 - 6mm	5mm	50	Box

HEAT SHRINKABLE FULLY INSULATED FEMALE BULLET TERMINALS



- Material: Brass with copper sleeve
- High-density polyethylene (HDPE)
- Shrink temperature: +150 °C
- Operating temperature: - 40°C to + 105°C
- Max. voltage: 300V
- Double crimp

BOX



PRODUCT INFORMATION

Part No.	Colour	Wire Size	Tab Size	Qty	Packaging
LV2815	Red	2.5 - 3mm	4mm	50	Box
LV2816	Blue	4mm	5mm	50	Box
LV2817	Yellow	5 - 6mm	5mm	50	Box