

LV1719

Blue Solar MPPT Charge Controller 35A

- Ultra fast Maximum Power Point Tracking
- Automatic Voltage Select - 12V, 24V & 48V
- Fully programable Algorithm
- Maximum Panel Input Voltage: 150V
- Real time data display option - Apple & Android Smart Phones
- Protection: Reverse Polarity
Output Short Circuit
Over Temperature
- Operating Temperature: -20°C to +50°C
- Dimensions: 130 x 186 x 70mm
- Weight: 1.25Kg
- Optional Programming Cable Part No. **LV1724**



LOW VOLTAGE

LV1723

Blue Solar MPPT Charge Controller 50A

- Ultra fast Maximum Power Point Tracking
- Automatic Voltage Select - 12V or 24V
- Fully programable Algorithm
- Maximum Panel Input Voltage: 100V
- Real time data display option - Apple & Android Smart Phones
- Protection: Reverse Polarity
Output Short Circuit
Over Temperature
- Operating Temperature: -20°C to +50°C
- Dimensions: 130 x 186 x 70mm
- Weight: 1.25Kg
- Optional Programming Cable Part No. **LV1724**



LOW VOLTAGE

LV1724

Programming Cable

- Suits Blue Solar MPPT Charge Controllers
- Downloadable Software available from the Victron Energy website



LOW VOLTAGE