

SHUTDOWN SOLENOIDS

SINGLE PACK



AXS15120 12V ENGINE SHUTDOWN SOLENOID




- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 90° Mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 41A, hold current: 0.76A
- Pull rating: 12 Lbs, hold rating: 19 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 50.8mm
- Reference: 1504-12C2U1B1S1A



AXS15130 24V ENGINE SHUTDOWN SOLENOID



- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 90° Mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 22A, hold current: 0.37A
- Pull rating: 12 Lbs, hold rating: 19 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 50.8mm
- Reference: 1504-24C2U1B1S1A



AXS17310 12V ENGINE SHUTDOWN SOLENOID




- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 2 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 46A, hold current: 1.1A
- Pull rating: 24 Lbs, hold rating: 38 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 50.8mm
- Reference: 1751-12E2U1B1S1A



AXS17315 24V ENGINE SHUTDOWN SOLENOID



- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 2 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 25A, hold current: 0.5A
- Pull rating: 24 Lbs, hold rating: 38 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 50.8mm
- Reference: 1751-24E2U1B1S1A



AXS20529 12V ENGINE SHUTDOWN SOLENOID



- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 2 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 58A, hold current: 1.7A
- Pull rating: 37 Lbs, hold rating: 88 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 50.8mm
- Reference: 2001-12S2U1B2A



AXS20549 24V ENGINE SHUTDOWN SOLENOID



- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 2 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 31A, hold current: 0.6A
- Pull rating: 37 Lbs, hold rating: 88 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 50.8mm
- Reference: 2001-24S2U1B2A

