

LV5407

4 WAY COMPACT ATS FUSE BLOCK

- Voltage rating: 32Vdc max.
- Current rating: 30A/cct
- Common input
- Terminal: M4 screws
- Base material: PBT
- Cover material: PC
- Terminal material: Nickel plated copper
- Screw material: Stainless steel
- Wire size range: 1.5 to 4mm²
- Dimensions: 92.5(L) x 43.8(W) x 32.5(H)mm



SINGLE PACK



LV5408

8 WAY COMPACT ATS FUSE BLOCK

- Voltage rating: 32Vdc max.
- Current rating: 30A/cct
- Common input
- Terminal: M4 screws
- Base material: PBT
- Cover material: PC
- Terminal material: Nickel plated copper
- Screw material: Stainless steel
- Wire size range: 1.5 to 4mm²
- Dimensions: 146(L) x 43.8(W) x 32.5(H)mm



SINGLE PACK



LV5409

6 WAY COMPACT ATS FUSE BLOCK

- Voltage rating: 32Vdc max.
- Current rating: 30A/cct
- Terminal: M4 screws
- Base material: PBT
- Cover material: PC
- Terminal material: Nickel plated copper
- Screw material: Stainless steel
- Wire size range: 1.5 to 4mm²
- Individual power inputs
- Dimensions: 131.3(L) x 54.2(W) x 38.6(H)mm



SINGLE PACK



LV5402

4 WAY ATS FUSE BLOCK WITH LED FAULT INDICATORS

- Voltage rating: 32Vdc max.
- Current rating: 30A/cct
- Input stud: M5
- Output terminal: 4 x Push-on
- Base material: PBT
- Cover material: PC
- Terminal material: Nickel plated copper
- Dimensions: 85(L) x 47(W) x 36(H)mm



SINGLE PACK

