

S9LK SERIES

ROADVISION™

FEATURES

- S9LK Stealth Series 9" Driving Light with Halo DRL
- Blackout mounting hardware
- Better visibility in wet & dusty conditions
- Warm white light produced by 3W Osram LED's
- Multi-volt 10-30V DC input & low current draw
- 50,000 hour LED lifespan with solid state technology
- Thermal Management Technology
- Light weight tough die-cast aluminium housing & polycarbonate lens
- Water & dust proof IP67 rated
- Over/under voltage, reverse polarity protection & EMI/EMC
- Radio interference approved

LOW KELVIN 4000K

LED DRIVING LAMPS



THERMAL
MANAGEMENT
TECHNOLOGY



HALO DRL
RING



MULTI-VOLT
10-30 VDC



POLYCARB
LENS



COLOUR
TEMP
4000K



WATERPROOF
IP67



OVER/UNDER
VOLTAGE
PROTECTION



REVERSE
POLARITY
PROTECTION



DEUTSCH
CONNECTOR



OSRAM
LEDS



EMI
EMC
RADIO
INTERFERENCE
APPROVED




7YR
WARRANTY

Roadvision's S9LK Stealth Series Driving Lights feature a warmer light colour and wider beam pattern. Perfect for larger 4wd's and trucks, the S9LK Stealth Series deliver better visibility in wet & dusty conditions, while dramatically reducing road sign flare. Featuring black mounting hardware, an innovative HALO DRL, and stylish bezel-less design, they deliver a sleek modern appearance. With 34 x 3W Osram LEDs, the S9LK Stealth Series punches out an impressive 9594lm per light and 493m of beam penetration @ 1 lux using Roadvision's Thermal Management Technology. Built to withstand the harshest conditions, the S9LK Stealth Series feature a tough yet lightweight aluminium housing and polycarbonate lens for superior performance and durability.

PART NUMBERS



RDL6900LK
9" LED Driving Light 10-30V Round 160W Combination Beam



SPECIFICATIONS

RDL6900LK

BEAM PATTERN	Combination
MAXIMUM LUMENS PER LIGHT (PAIR)	9,594lm (19,188lm)
MAXIMUM LUX @ 10M PER LIGHT (PAIR)	2,430lx (4,860lx)
MAXIMUM BEAM DISTANCE @ 1LX PER LIGHT (PAIR)	493m (697m)
MAXIMUM BEAM DISTANCE @ 0.5LX PER LIGHT (PAIR)	697m (986m)
INPUT VOLTAGE	10-30VDC
MAXIMUM WATTS	160W
NUMBER OF LEDS	34 x 3W Osram
CURRENT DRAW @ 13.8V	11.64 Amps
LENS CONSTRUCTION	Polycarbonate
HOUSING CONSTRUCTION	Die-Cast Aluminium
WIRING	2 Pin Deutsch Plug
DIMENSIONS AXBXC	238 x 87 x 249mm

LINE DIAGRAM

