

2022-ON NEXT GEN FORD RANGER HIGH BEAM PATCH HARNESS

INSTALLATION INSTRUCTIONS

Note: Before attempting to install driving lights on your 2022-on Ford Ranger, we strongly recommend consulting with a professional if necessary.

Headlight Identification: Identify the type of headlamp on your vehicle to determine the installation method.



LEVEL 1
LOW-LEVEL HEADLIGHTS



LEVEL 2
MID-LEVEL HEADLIGHTS
NOTE: RHBT23 HARNESS NOT REQUIRED
PICKUP VIA LHS FOOT WELL



LEVEL 3
HIGH-LEVEL HEADLIGHTS

LEVEL 1 AND LEVEL 3: HEADLIGHTS REQUIRE THE ROADVISION RHBT23 HIGH BEAM PATCH HARNESS.

- Connect the Roadvision RHBT23 High Beam Patch Harness in-line between the LH headlight and the vehicle harness.
- Bolt the M6 lug to an appropriate earth point.
- The Roadvision RHBT23 High Beam Patch Harness will have 2 clearly labelled plugs indicating:
Level 1 - **High Beam Level 1(C1-4)** and Level 3 - **High Beam Level 3(C1-13)**.
Connect to the corresponding plug for that matches your headlight configuration.
- To safeguard your vehicle's electronics, it is crucial to use a relay in your installation. We highly recommend using a fully compatible Roadvision wiring harness. Choose from the following options depending on your accessory:
 - **RDWK** – For Driving Lights
 - **RBWK** – For Light Bars with DT connector
 - **RBHDWK** – For Light Bars with ATP connector